



ADSDUPIVRC
Vandal Resistant Indoor Dome
Housing

ADSDUPIHC
Indoor Dome Housing

SpeedDome® Ultra

Indoor Dome Housing

Features:

- Reinforced high impact design
- Vandal resistant option
- Compact, attractive design
- Four tamper-proof screws with driver bit supplied
- Ceiling, pole, roof, wall and corner mounts available

The SpeedDome Ultra indoor dome housing allows the SpeedDome Ultra dome to be installed indoors using the same design as found in the SpeedDome Ultra outdoor housing. It is available in standard and vandal resistant options.

The housing is made of a reinforced fiberglass high impact polycarbonate material along with a UV stabilized trim ring and top cover. The bubble assembly is affixed to the top via tamper-proof screws.

For applications where vandalism is a concern, a vandal resistant model is available which includes an aluminum sunshield cover and a high impact bubble which meets ANSI-87.1 impact safety standards. For additional protection a stainless steel bubble cage is provided.

Simply add an interface board, plug in the video cable, connect power and data, and install any SpeedDome Ultra. Diagnostic power and communications LEDs confirm proper connection and aid in troubleshooting. A variety of mounts accommodate the housing, making it easy to install.

The housing supports both the RUPTB and RUIOB dome bases (not included) and is supplied with either a choice of a clear or smoked bubble.

Model Numbers

ADSDUPIHC	Indoor Ultra Housing with clear bubble (f0)
ADSDUPIHS	Indoor Ultra Housing with smoked bubble (f1.0)
ADSDUPIVRC	Vandal Resistant Indoor Ultra Housing with high-impact clear bubble (f0)
ADSDUPIVRS	Vandal Resistant Indoor Ultra Housing with high-impact smoked bubble (f1.0)

Weight

Without Dome	2.30 kg
With Dome	3.50 kg
Shipping Weight of Housing	4.00 kg
Mechanical Connection	1.5 inch NPT

Environmental

Operating Temperature	10° to 50° C
Humidity	0 to 95% RH (non-condensing)
Storage Temperature	20° to 65° C

Mechanical










ADSDUPIHC, ADSDUPIHS

Construction	
Enclosure	Aluminum Sun Shade, Trim Ring,
Top Cover	UV stabilized polycarbonate
Colour	Light grey
Height	321 mm
Diameter	244 mm
Bubble	Acrylic
Bubble Diameter	75.3 mm
Weight	
Without Dome	1.6 kg
With Dome	2.8 kg
Shipping Weight of Housing	3.3 kg
Mechanical Connection	1.5 in NPT

ADSDUPIVRL, ADSDUPIVRS

Construction	
Enclosure	Aluminum Sun Shade, Trim Ring,
Top Cover	UV stabilized, polycarbonate
Sun Shade Cover	Aluminum with high gloss power coating
Colour	Light grey
Height	321 mm
Diameter	244 mm
Bubble	High impact acrylic
Bubble Diameter	75.3 mm
Bubble Cage	Stainless steel, painted flat black
Height	87.7 mm
Width	212 mm

Mounts and Adapters

<p>RHOSW Indoor/outdoor short wall mount with end cap assembly</p> 	<p>RHOLW Indoor/outdoor long wall mount with end cap assembly</p> 
<p>RHOWPA Indoor/outdoor pole strap adapter for RHOSW and RHOLW</p> 	<p>RHOWCA Indoor/outdoor corner bracket adapter for RHOSW and RHOLW</p> 
<p>ROENDC Indoor/outdoor end cap assembly adapter</p> 	<p>RHOPN Indoor/outdoor pendant mount</p> 
<p>RHOTR Outdoor over-the-roof mount with end cap assembly</p> 	<p>ROTRF Outdoor floor adapter for RHOTR</p> 
<p>RHIUB Indoor I-beam clamp</p> 	

For further information on how ADT can help you, contact your local office or phone free on **0800 010 999** or visit us at www.adt.co.uk



Head Office: ADT Fire and Security plc, Security House, The Summit, Hanworth Road, Sunbury-on-Thames, Middlesex TW16 5DB.
ADT and the ADT logo are registered trademarks of ADT Services AG and are used under license.
ADT reserves the right to modify or withdraw any product or service without notice.

Ref No PSS100A Issue 2 August 2006

© 2006 Tyco International



ADT Always There®