



ADSDUPIVRC
Vandal Resistant Indoor Dome
Housing

ADSDUPIHC
Indoor Dome Housing

SpeedDome® Ultra Indoor Dome Housing

Features:

- Reinforced high impact design
- Vandal resistant option
- Compact, attractive design
- Four tamper-proof screws with driver bit supplied
- Ceiling, pole, roof, wall and corner mounts available

The SpeedDome Ultra indoor dome housing allows the SpeedDome Ultra dome to be installed indoors using the same design as found in the SpeedDome Ultra outdoor housing. It is available in standard and vandal resistant options.

The housing is made of a reinforced fiberglass high impact polycarbonate material along with a UV stabilized trim ring and top cover. The bubble assembly is affixed to the top via tamper-proof screws.

For applications where vandalism is a concern, a vandal resistant model is available which includes an aluminum sunshield cover and a high impact bubble which meets ANSI-87.1 impact safety standards. For additional protection a stainless steel bubble cage is provided.

Simply add an interface board, plug in the video cable, connect power and data, and install any SpeedDome Ultra. Diagnostic power and communications LEDs confirm proper connection and aid in troubleshooting. A variety of mounts accommodate the housing, making it easy to install.

The housing supports both the RUPTB and RUIOB dome bases (not included) and is supplied with either a choice of a clear or smoked bubble.

SPECIFICATIONS

Model Numbers

ADSDUPIHC	Indoor Ultra Housing with clear bubble (f0)
ADSDUPIHS	Indoor Ultra Housing with smoked bubble (f1.0)
ADSDUPIVRC	Vandal Resistant Indoor Ultra Housing with high-impact clear bubble (f0)
ADSDUPIVRS	Vandal Resistant Indoor Ultra Housing with high-impact smoked bubble (f1.0)

Mechanical

ADSDUPIHC, ADSUPIHS

Construction	
Enclosure	Aluminum Sun Shade, Trim Ring,
Top Cover	UV stabilized polycarbonate
Colour	Light grey
Height	321 mm
Diameter	244 mm
Bubble	Acrylic
Bubble Diameter	75.3 mm
Weight	
Without Dome	1.6 kg
With Dome	2.8 kg
Shipping Weight of Housing	3.3 kg
Mechanical Connection	1.5 in NPT

ADSDUPIVRL, ADSUPIVRS

Construction	
Enclosure	Aluminum Sun Shade, Trim Ring,
Top Cover	UV stabilized, polycarbonate
Sun Shade Cover	Aluminum with high gloss power coating
Colour	Light grey
Height	321 mm
Diameter	244 mm
Bubble	High impact acrylic
Bubble Diameter	75.3 mm
Bubble Cage	Stainless steel, painted flat black
Height	87.7 mm
Width	212 mm
Weight	
Without Dome	2.30 kg
With Dome	3.50 kg

Shipping Weight of Housing

4.00 kg

Mechanical Connection

1.5 inch NPT

Environmental

Operating Temperature 10° to 50° C

Humidity 0 to 95% RH (non-condensing)


Storage Temperature 20° to 65° C

Mounts and Adapters

RHOSW Indoor/
outdoor short wall
mount with end cap
assembly




RHOLW Indoor/outdoor
long wall mount
with end cap
assembly




RHOWPA Indoor/outdoor pole
strap adapter for
RHOSW and
RHOLW



RHOWCA Indoor/outdoor
corner
bracket adapter
for RHOSW and
RHOLW




ROENDC Indoor/outdoor
end cap assembly
adapter




RHOPN Indoor/outdoor
pendant mount



RHOTR Outdoor over-the-roof
mount with end cap
assembly



ROTRF Outdoor floor
adapter
for RHOTR



RHIUIB Indoor I-beam
clamp



For further information on how we can help you please visit our website at www.tycofis.com or e-mail us on tycofis@tycoint.com. The right is reserved to modify or withdraw any product or service without notice. PSS100TFIS Issue 2 August 2006 © 2006

tyco

Fire & Integrated
Solutions

a vital part of your world