

AD Manual Iris Lenses



Features:

- 1/3-inch
- C and CS mounts
- Colour corrected optics
- High quality, compact design
- Fixed and variable focal lengths
- Right angle and straight pinhole versions
- Slip clutch on lens mount for easy positioning

The comprehensive line of AD manual iris lenses provides cost effective solutions to applications where scene and lighting requirements are relatively stable. Manual iris lenses can also provide very cost effective solutions when used with cameras equipped with electronic shutters. Modern CCD imagers place new demands on lens performance in terms of resolution, contrast, and geometric distortion. All AD lenses provide high contrast, fast signal response, and high quality colour corrected optics.

Pinhole lenses are available in straight or right angle configurations for covert applications where the use of standard diameter lenses would compromise the observation location.

Specifications

| Model Numbers | Focal Length | Aperture (f Stop) | Lens Format | Mount | View Angle | | Minimum Object Distance | Filter Screw Size | Weight | Size (Diameter x Length) |
|--------------------------------------------|--------------|-------------------|-------------|-------|--------------|--------------|-------------------------|-------------------|--------|--------------------------|
| | | | | | Horizontal | Vertical | | | | |
| Fixed Focal Length – Manual Iris | | | | | | | | | | |
| L2616CS | 2.6 mm | f1.6 - 11C | 1/3-inch | CS | 98.7° | 74.9° | 0.1 M | NA | 45 g | 34.5 x 34.7 mm |
| L0412CS | 4.0 mm | f1.2 - 16C | 1/3-inch | CS | 63.9° | 49.1° | 0.2 M | 30.5 X 0.5 mm | 36 g | 34.5 x 33 mm |
| L0812CS | 8.0 mm | f1.2 - 16C | 1/3-inch | CS | 34.7° | 25.9° | 0.2 M | 30.5 X 0.5 mm | 37 g | 34.5 x 33 mm |
| L3616CS | 3.6 mm | f1.6 - 16C | 1/2-inch | CS | 99.2° | 74.1° | 0.2 M | 30.5 X 0.5 mm | 38 g | 34.5 x 33 mm |
| L0614CS | 6.0 mm | f1.4 - 16C | 1/2-inch | CS | 58.3° | 44.3° | 0.2 M | 30.5 X 0.5 mm | 35 g | 34.5 x 33 mm |
| L1214CS | 12.0 mm | f1.4 - 16C | 1/2-inch | CS | 30.4° | 22.7° | 0.3 M | 30.5 X 0.5 mm | 33 g | 34.5 x 33 mm |
| Variable Focal Length – Manual Iris | | | | | | | | | | |
| L35814CS | 3.5 - 8 mm | f1.4 - C | 1/3-inch | CS | 77.5 - 35.4° | 57.6 - 26.6° | 0.4 M | NA | 138 g | 34 x 43.5 mm |
| L41015CS | 4.5 - 10 mm | f1.5 - C | 1/2-inch | CS | 85.3 - 37.7° | 62.1 - 28.2° | 0.3 M | 43.0 x 0.75 mm | 120 g | 45 x 54.6 mm |

For further information on how ADT can help you, contact your local office or phone free on **0800 010 999** or visit us at www.adt.co.uk



Head Office: ADT Fire and Security plc, Security House, The Summit, Hanworth Road, Sunbury-on-Thames, Middlesex TW16 5DB.
 ADT and ADT Always There is a registered trademark of ADT Services AG and used under license.
 ADT reserves the right to modify or withdraw any product or service without notice.

Ref No PSS124A Issue 2 July 2006

© 2006 Tyco International



ADT Always There®