



YV2.8×2.8SA-2

Megapixel Rated Lens

Features

- High image-quality monitoring with optical performance
- WIDE 2.8mm, achieving a horizontal field angle of 100 degrees (when used on 1/3 cameras).
- Compact and lightweight design.
- Designed to maximize optical performance with high-accuracy aspheric lens, low-dispersion glass, and high refractive-index glass.

Technical Information

Focal Length (mm)		2.8 - 6 (2.8x)	
Iris Range		F1.2 - Close	
Operation	Zoom	Manual	
	Focus	Manual	
	Iris	Manual	
Angle of view (HXV)	1/3"	WIDE	100°00" x 73°45"
		TELE	35°03" x 26°18"
	1/4"	WIDE	73°45" x 54°49"
		TELE	26°18" x 19°44"
Focusing Range From Front Of The Lens) (m)		∞ - 0.3	
Object Dimension at M.O.D (HxV) (mm)	1/3"	WIDE	744 x 468
		TELE	197x 146
	1/4"	WIDE	468 x 323
		TELE	146 x 108
Back Focal Distance (in air) (mm)		7.70	
Exit Pupil Position (From Image Plane) (mm)		314	
Filter Thread (mm)		—	
Mount		CS	
Mass (g)		50	
Remarks		. With Metal Mount	

Ordering information

YV2-8X2-8SA-SA2 Fujinon 2.8-8mm DC auto iris megapixel rated lens

For further information on how ADT can help you, contact your local office or phone free on **0800 010 999** or visit us at www.adt.co.uk

CE

Head Office: ADT Fire and Security plc, Security House, The Summit, Hanworth Road, Sunbury-on-Thames, Middlesex TW16 5DB.
ADT and the ADT logo are registered trademarks of ADT Services AG and are used under license.
ADT reserves the right to modify or withdraw any product or service without notice.

Ref No PSS336A Issue 1 March 2010

© 2010 Tyco International



ADT Always There®