



YV3.3×15SA-2

Vari-Focal Lens

Features

- High image-quality monitoring with optical performance
- f15-50mm, 3.3x zooming application compatible lens.
- Designed to maximize optical performance with high-accuracy aspheric lens, low-dispersion glass, and high refractive-index glass.

Technical Information

Focal Length (mm)		15 - 50 (3.3x)	
Iris Range		F1.5 - Close	
Operation	Zoom		Manual
	Focus		Manual
	Iris		Manual
Angle of view (HXV)	1/3"	WIDE	18°08" x 13°34"
		TELE	5°35" x 4°12"
	1/4"	WIDE	13°34" x 10°10"
		TELE	4°12" x 3°10"
Focusing Range From Front Of The Lens) (m)		∞ - 0.8	
Object Dimension at M.O.D (HxV) (mm)	1/3"	WIDE	271 x 202
		TELE	87x 66
	1/4"	WIDE	202 x 151
		TELE	66 x 49
Back Focal Distance (in air) (mm)		MIN 7.7	
Exit Pupil Position (From Image Plane) (mm)		-36	
Filter Thread (mm)		-	
Mount		CS	
Mass (g)		60	
Remarks		. With Metal Mount	

Ordering information

YV3-3x15SA-SA2 Fujinon 15-50mm DC auto iris megapixel rated lens

For further information on how ADT can help you, contact your local office or phone free on **0800 010 999** or visit us at www.adt.co.uk

CE

Head Office: ADT Fire and Security plc, Security House, The Summit, Hanworth Road, Sunbury-on-Thames, Middlesex TW16 5DB.
ADT and the ADT logo are registered trademarks of ADT Services AG and are used under license.
ADT reserves the right to modify or withdraw any product or service without notice.

Ref No PSS337A Issue 1 March 2010

© 2010 Tyco International



ADT Always There®