



## YV4.3×2.8SA-2

### Vari-Focal Lens

#### Features

- High image-quality monitoring with optical performance
- Wide f2.8-12mm range accommodates various applications
- Designed to maximize optical performance with high-accuracy aspheric lens, low-dispersion glass, and high refractive-index glass.

## Technical Information

Focal Length (mm)		2.8 - 12 (4.3x)	
Iris Range		F1.4 - Close	
Operation	Zoom	Manual	
	Focus	Manual	
	Iris	Manual	
Angle of view (HXV)	1/3"	WIDE	100°02" x 74°03"
		TELE	23°26" x 17°36"
	1/4"	WIDE	74°03" x 55°06"
		TELE	17°36" x 13°13"
Focusing Range From Front Of The Lens) (m)		∞ - 0.3	
Object Dimension at M.O.D (HxV) (mm)	1/3"	WIDE	753 x 476
		TELE	131 x 98
	1/4"	WIDE	476 x 329
		TELE	98 x 73
Back Focal Distance (in air) (mm)		7.83	
Exit Pupil Position (From Image Plane) (mm)		455	
Filter Thread (mm)		—	
Mount		CS	
Mass (g)		80	
Remarks		. With Metal Mount	

## Ordering information

YV4-3x2-8SA-SA2 Fujinon 2.8-12mm DC auto iris megapixel rated lens

For further information on how ADT can help you, contact your local office or phone free on **0800 010 999** or visit us at [www.adt.co.uk](http://www.adt.co.uk)

CE

Head Office: ADT Fire and Security plc, Security House, The Summit, Hanworth Road, Sunbury-on-Thames, Middlesex TW16 5DB.  
ADT and the ADT logo are registered trademarks of ADT Services AG and are used under license.  
ADT reserves the right to modify or withdraw any product or service without notice.

Ref No PSS338A Issue 1 March 2010

© 2010 Tyco International



ADT Always There®