



Sensormatic® Ultra-Exit 2M

Features:

- Open frame, high impact ABS design provides line of sight into the store while preserving aesthetics over time.
- Up to 8 metre coverage from one controller with 2 metre coverage between pedestals.
- Ultra-Max 9050 Controller platform provides advanced DSP, connectivity, efficient power management, software controlled system configuration, separate alarm relays and up to four transceivers from one controller.
- Antenna Options include bases constructed high impact ABS and stainless steel as well as ABS moulded edge bumpers for harsh environments.
- Audible and visual alarms provide notification of identified events.
- SmartEAS Options include people counting sensors integrated to the alarm lens and alarm counting.
- Ultra-Max Detection for the range of Sensormatic hard tags and labels.

The Sensormatic® Ultra-Exit 2M provides retailers with high performance, high value Ultra-Max EAS protection over wide exits.

The open frame design and two metre separation of antenna preserves an open store appearance. Constructed of high impact ABS material, the Ultra-Exit 2M will maintain its integrity and aesthetics in even the most demanding of retail environments.

Accurate and consistent performance is provided by the Ultra-Max 9050 Controller. This detection platform uses parallel resonance technology, the latest DSP and efficient power management to deliver high level performance and functionality.

Specifications

Transmitter

Operating Frequency	58kHz (±200Hz)
Transmit Burst Duration	1.6ms
Max. Transmit Current	16A peak
Burst Repetition Rate	
Based on 50Hz ac	75Hz or 37.5Hz
Based on 60Hz ac	90Hz or 45Hz

Receiver

Center Frequency	58kHz
Receive Coil Resistance	1.6 ohms (±5%)

Alarm

Audio level	83dBA
-------------	-------

Environmental

Ambient Temperature	0°C to 50°C
Relative Humidity	0 to 90% Non-condensing

Mechanical

Height	155cm
Width	50.9cm
Thickness (with base covers)	12.5cm
Weight (with base covers)	9.7kg

Regulatory Compliance

EMC	47 CFR, Part 15 ETSI EN 300 330 ETSI EN 301 489 RSS-310
Safety	UL 60950-1 CSA C22.2 No.60950-1 EN 60950-1

Product Compatibility

The Ultra·Exit 2M is powered by the Ultra·Max 9050 Controller.

Antenna Product Code

ZS1090	Ultra·Exit 2M
--------	---------------

Antenna Option Product Codes

ZPUE-PLBASE	Ultra·Exit Base Cover - Dark Grey
ZPUE-PLBASE-MS	Ultra·Exit Base Cover - Silver Grey
ZPUE-SSBASE 1	Ultra·Exit Stainless Steel Base Cover
ZPUE-BUMPER	Ultra·Exit Bumper Kit - Dark Grey
ZPUE-TRAFFICNTR	Ultra·Exit Traffic Counting Sensor Set
ZPUE-ALMCNTR	Ultra·Exit Alarm Counter Kit

Controller Product Code

ZE9050	Ultra·Max 9050 Controller
--------	---------------------------

Ultra·Max® EAS systems are designed to detect the range of Sensormatic® tags and labels. Specification for performance is based on the Ultra®Strip III label.

For further information on how ADT can help you, contact your local office or phone free on **0800 010 999** or visit us at www.adt.co.uk

CE

Head Office: ADT Fire and Security plc, Security House, The Summit, Hanworth Road, Sunbury-on-Thames, Middlesex TW16 5DB.
ADT and the ADT logo are registered trademarks of ADT Services AG and are used under license.
ADT reserves the right to modify or withdraw any product or service without notice.

Ref No PSE04 1A Issue 2 September 2009

© 2009 Tyco International



ADT Always There®