



VE1120 Series

PIR Detector with 11 curtains of 20m

Features:

- Passive Infra Red motion sensor
- Tri-Brid Step & Gliding Focus Curtain mirror
- Plug-in electronics
- Sealed optics
- "V2E" signal processing for false alarm immunity
- Cloak and umbrella immunity
- Full under crawl detection
- Selectable coverage pattern using mirror masks
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- Complies with EN50131-2-2 Grade 2
- Several European approvals

GE Security motion sensors have the most advanced and sophisticated optics in the security industry. This unique optical mirror technology is a step and gliding focus, which creates a continuous curtain resulting in a sensor that never loses track of the object.

To increase detection coverage, the VE1120 series sensors incorporate a 3-step gliding focus, which produces 11 continuous curtains to detect infrared signals up to a 20m distance.



VE1 120 Series

Infrared signals are captured by the pyro-electric sensor that is placed in the detectors' focal point. The conventional pyro generates a one-dimensional signal (value) to detect the presence of a source, and therefore its detection probability within the area is entirely determined by the resolution of the optics of the motion detector.

Patented Vector pyro

Due to the unique construction of the patented Vector pyro, a thermal source will generate a multi-dimensional signal (vector), allowing the pyro to determine not only the presence but also the direction of motion of a thermal source. This now means that the detection probability is equal to the product of the resolution of the optics and the multi-dimensional output of the pyro. This is a major advance in PIR technology capability.

V2E signal processing

The VE series of motion detectors incorporate a patented Vector Verified Enhanced (V2E) signal processing. Each type of signal source will generate a unique vector output captured by the Vector pyro.

The digital signal processing will analyze each vector's shape and pattern, allowing it to distinguish different signal sources. It means that VE series motion sensors will not only identify non-thermal signal sources, but also filter out any potential nuisance signals such as stationary thermal sources, ventilators or strong light sources, and react only to alarm signals from intruders. PIR motion sensor with vector pattern recognition is unique to GE Security.

Easy to install

PIRs of the 1000 series are the most rewarding sensors to install:

1. Tolerate wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of vision.
3. No range setting is required thanks to constant range sensitivity.
4. Plug-in electronics.

Complete family

The 1000 series are part of the GE Security range of motion sensors. This family includes motion sensors with variants in housing size, detection range, anti-masking, dual detection technology, addressable interfacing, wireless transmission and more. This range covers all applications where security needs to be safeguarded.

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

Specifications

Detection range	20 m
Undercrawl protection	Yes
Sensitivity	Normal / High
Coverage field of view	86° with 11 curtains
Coverage pattern selection	Curtain labels
Mounting height	1.8 to 3.0 m (6 to 10 ft)
Power supply	9 to 15 VDC
Current consumption (nom.)	4.4 mA
Alarm relay (voltage free)	NC when energised
Tamper relay (voltage free)	NC when cover closed
Remote control lines	Walk test
Alarm memory	Yes
PIR signal processing	V2E
Dimensions (W x H x D)	125 x 65 x 60 mm
Ambient conditions	-10 to +55°C; 95% relative humidity
Pry-off tamper	Optional
EN50131-2-2	Grade 2

Ordering Information

VE1120S70	"Tri-Brid Step & Gliding Focus Multi Curtain" mirror optics passive infra red detector, with "V2E" signal processing for false alarm immunity, wide angle (86° with 11 curtains) selectable range up to 20m, NC relay
VE1120AMS70	"Tri-Brid Step & Gliding Focus Multi Curtain" mirror optics passive infra red detector, with "V2E" signal processing for false alarm immunity, wide angle (86° with 11 curtains) selectable range up to 20m, NC relay, antimask
816.005.001	SB01 Mounting bracket for EV-detectors

Detection Pattern



For further information on how we can help you, contact your local ADT office:

Austria - ADT Austria
Tel: 662 45 24 60 11
Website: www.adteurope.com

Belgium - ADT Security Services SA.
Tel: 02 481 08 00
Website: www.adt-belguim.be

Czech Republik - ADT Security Center s.r.o.
Tel: 267 267 267
Website: www.adt-sc.cz

Denmark - ADT A/S
Tel: 70 80 70 00
Website: www.adt-nordic.com

France - ADT France
Tel: 0810 000 260
Website: www.adtfrance.fr

Germany - ADT Deutschland GmbH
Tel: 0800 7070 238
Website: www.adt-deutschland.de

Greece - ADT Greece SA
Tel: 210 92 43 400
Website: www.adt.gr

Ref No PSI289AEU Issue 1 March 2009
© 2009 Tyco Fire & Security plc

Hungary - ADT Hungary
Tel: +3614303700
Website: www.adthungary.com

Ireland - ADT Fire and Security plc
Tel: 1620 5888
Website: www.adt.ie

Italy - ADT Italy
Tel: 02 818061
Website: www.adtitaly.com

The Netherlands - ADT Security Services B.V.
Tel: 010 258 4848
Website: www.adt-security.nl

Norway - ADT AS NUF
Tel: 81 55 88 88
Website: www.adt-nordic.com

Poland - ADT Poland Sp. Z o.o.
Tel: 0 801 801 238
Website: www.adt.pl

Portugal - ADT Portugal
Tel: 217 510 560
Website: www.adt-pt.com

Russia - ADT Russia
Tel: +7 (495) 661 2094
Website: www.adtrussia.com

Spain - ADT Servicios de Seguridad SL
Tel: 902 444 440
Website: www.adt-es.com

Sweden - ADT AB
Tel: 8 40 00 70 00
Website: www.adt-nordic.com

Switzerland - ADT Switzerland
Tel: 0848 40 08 01
Website: www.adt-ch.com

United Kingdom - ADT Fire & Security plc
Tel: 0800 010 999
Website: www.adt.co.uk



ADT Always There®