



## Small Public Address System

Single Zone Desk Top

Microphone - 2571/040

### Features:

- Suitable for passive or electronic access amplifiers
- Microphone incorporates speech blast screen
- Soft touch press-to-talk button with minimal noise transfer
- All steel construction, weighted base, finished in scratch and chip resistant powder coat paint
- Anti-slip feet - the microphone will not scratch or mark the desk/console
- Fitted with a moving coil microphone capsule, perfect for most amplifier input sensitivities. For less sensitive amplifiers an electret version is available; requires DC powering from host amplifier
- 2.5 metre lead (free end)

### Ideal for applications

- Shops
- Offices
- Garages
- Transport terminals

### 2571/040 - Single Zone Desk Top Microphone

The simple but robust microphone features a gooseneck mounted microphone well known for its voice clarity in almost any operating environment.

Used in all our system packages for your "off the shelf" Public Address solution

## SPECIFICATIONS

### Technical Information

Microphone	Moving Coil
Sensitivity	Suitable for all amplifiers with at least 500uV (0.5mV) sensitivity
Impedance	600 Ohms
Characteristics	Polar diagrams approximates to cardioid, presence lift at 3kHz
Frequency response	100Hz~12khz
Press to talk	"Soft touch" momentary action, push button (two on two zone)
Cabling Supplied	2.5 metre screened microphone pairplus access pair/s
Dimensions - base	140(D) x 110(W) x 40 (max H) mm
Dimensions Gooseneck	260mm length to capsule
Weight	700g
Finish - desk top	Pear white powder coat
Finish - desk - base	Satin black powder coat
Finish	
- Gooseneck & microphone	Matt black

For further information on how we can help you please visit our website at [www.tycofis.com](http://www.tycofis.com) or e-mail us on [tycofis@tycoint.com](mailto:tycofis@tycoint.com). The right is reserved to modify or withdraw any product or service without notice. PSPV061TFIS Issue 1 March 2007 © 2007

**tyco**

*Fire & Integrated  
Solutions*

*a vital part of your world*